



# Le | SERIES

ELECTRIC TRUCKS

MY27 L6e/L7e

**MORE THAN  
A TRUCK**



**INSTANT POWER.  
PROVEN STRENGTH.**

# Le | SERIES

## ELECTRIC TRUCKS

MY27 L6e/L7e



### MOTOR/DRIVETRAIN/AXLE

Accelerata Integrated eAxle 14Xe Gen 4.5	
Peak Power	260 kW / 348 hp
Continuous Power	180 kW / 241 hp
Transmission	Integrated Two-Speed Automatic

### BATTERIES & HV SYSTEM

HV Battery System	Hexagon Purus ProPack™
Battery Cell	Panasonic Energy Lithium Ion
Battery Capacity (Total / Usable)	269 kWh / 238 kWh
System Voltage	750V Max System Voltage
DC Fast Charging	Up To 120kW
DC Charger Type	CCS Type 1
AC Level 2 Charging	80 Amp 240V Level 2 Charging 19.2 kW
Charging Time (MAX DC)	1.8 Hours (0-80% SOC @ 120 kW)
Charging Time (MAX AC)	9.2 Hours (0-80% SOC @ 19.2 kW)

### RATINGS & CAPACITIES

GVWR	25,950 Lbs. / 33,000 Lbs.
Service Brake System Type	Air Bendix ADB22X 22.5 in. ConMet Disc
Front Axle	Dana Spicer E-Series, 12,500 Lbs.
Rear Axle	23,000 Lbs.
Front & Rear Tires	Bridgestone Rib 11R22.5 R268FZ G-Load
Frame Yield Strength	.354x10.16x3.50 in, 120Kpsi (RBM 1,877,214/Rail)

### POPULAR OPTIONAL EQUIPMENT

Back-up alarm
Mirrors, single arm fender mounted, outside rearview, power heated - chrome or black
Convex passenger side look down mirror
Power windows and door locks (with or without keyless entry)

\*Not all equipment combinations are compatible. For compatibility, additional options and specifications please visit your local Authorized Hino Trucks Dealer. Are you a body company? Additional information @ hinobodybuilder.com

Legal Disclaimer - The equipment and specifications shown are subject to change without notice. The information, content, and materials are presented "as is" at the time of publication, and no representations are made that the content is error-free. ©Hino Motors Sales U.S.A., Inc. All rights reserved. All other marks are trademarks of their respective owners.

### ELECTRICAL & SAFETY

Low Voltage System Maintenance Smart-Awake Active 12V Management
HV Safety Continuous HVIL + Emergency Active Discharge
Wabco 4S/4M ABS with Automatic Traction Control and Electronic Stability Control, Automatic Emergency Braking System (ZF OnGuardMax)
Driver And Passenger 3-Point Seat Belt, Black

### CAB & CHASSIS

Cab Type	Galvanized Steel Reinforced Two Door Day Cab
Wheelbase	253.00 in. / 271.00 in.
BBC	109.6in
Cab to Axle/Trunnion	185.5 in. / 203.8 in.

### STANDARD FEATURES

Bendix Air Disc Brakes	ADB22X
Air Dryer	Bendix AD-IS Air Dryer
Gear Selection	Push Button Electronic Shift Selector - Dash mounted
Driver's Seat	National 4-Way Adjustable High-Back Vinyl Air Suspension RH Arm Rest
Passenger's Seat	CVG 2/3 Width Vinyl Two Man Bench
Digital Instrument Cluster	Displays Speed, Range, and SOC
Regenerative Braking	10 Selectable Levels
Automatic Emergency Braking System (AEBS)	ZF OnGuardMAX

### WHAT TO EXPECT

Smooth Automotive Feel, Effortless Power
Cab Chassis Curb Weight : Under 14,000 Lbs.
Nearly Clear Frame Rails Back of Cab for Easy Upfit Options
Unparalleled Visibility

### SERVICES



Hexagon Purus ProPack™	HV Battery & EV System	3 yrs/150k Miles/350 Mh of Discharge
Accelerata	eAxle 14Xe Gen 4.5	2 yrs/200k Miles
HINOWATCH	24/7 Roadside Assistance	STD 3 Year

